

INDUSTRIAL COMPONENT DATA

RCDILE250-C 230268 XTMCXRSCB EATON ELECTRIC RC suppressor circuit, 250VAC, for DILE, spring clamp connection

Brand: EATON - MOELLER | Manufacturer Part Number: RCDILE250-C



Manufacturer	EATON - MOELLER
MPN / Reference	RCDILE250-C
Catalog number	XTMCXRSCB
Category	Surge protection module
Minimum order	10 Pcs
Document ID	EO-C296334258
Generated	2026-08-04

Product Overview

RC suppressor circuit, 250VAC, for DILE, spring clamp connection

RCDILE250-C

Eaton Moeller® series DILE RC suppressor circuit, 110 - 250 AC V, For use with: DILE...-C

RC suppressor circuit, Accessories: Suppressor circuit, Description: RC suppressor, Actuating voltage: Us 110 - 250 AC V, For use with: DILE...-C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILE Accessory RC suppressor circuit Catalog Number 230268 Model Code

RCDILE250-C EAN 4015082302689 Product Length/Depth 16 mm Product Height 29 mm Product Width 33 mm Product

Weight 0.009 kg Certifications CSA File No.: none

CSA-C22.2 No. 14-05

CE

UL 508

IEC/EN 60947-4-1

UL File No.: E29184

UL Category Control No.: NKCR2

UL Recognized Features & Functions

Functions RC-element General

Product category Accessories Used with DILE...-C Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 250 V Rated control supply voltage (Us) at AC, 50 Hz - max 250 V

Rated control supply voltage (Us) at AC, 60 Hz - min 250 V Rated control supply voltage (Us) at AC, 60 Hz - max 250 V

Rated control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,

current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,

non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to n...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / RCDILE250-C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.