

INDUSTRIAL COMPONENT DATA

Z-LAR32-S 248261 Y7-248261 EATON ELECTRIC Release relay, 250VAC, 1N/O, 15-32A, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-LAR32-S



Manufacturer	EATON - MOELLER
MPN / Reference	Z-LAR32-S
Catalog number	Y7-248261
Category	Load shedding relay for distribution board
Minimum order	1 Pcs
Document ID	EO-8C1918D879
Generated	2026-08-06

Product Overview

Release relay, 250VAC, 1N/O, 15-32A, 1HP

Z-LAR32-S

Eaton Distribution parts. Release relay, 250VAC, 1N/O, 15-32A, 1HP

Load shedding (current) relay, rated current range 15-32A, integrated auxiliary contact: 1 N/O, rated operating voltage 250V, rated insulation voltage 440V, rated impulse withstand voltage 4 kV, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section main circuit 2x10 mm², terminal cross-section auxiliary circuit 2x2.5 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 248261 Model Code Z-LAR32-S EAN 4015082482619 Product Length/Depth 80 mm Product Height 70 mm Product Width 17.5 mm Product Weight 0.109 kg Compliances RoHS conform Product specifications

Mounting method DIN rail Current rating of control contacts 1 A Just-operate current - max 32 A Just-operate current - min 15 A Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 1 Number of electrical switching cycles per hour - max 3600 Rated operational voltage (Ue) - max 250 V Rated uninterrupted current (Iu) 32 A Rated uninterrupted current (Iu) - max 32 A Rated uninterrupted current (Iu) - min 15 A Switching power of control contacts - max 7.36 VA Switching voltage of control contacts - max 250 V Switch-off

time delay - max 0 ms Width in number of modular spacings 1 Built-in depth 60 mm Degree of protection IP20 Lifespan, electrical 100000 c (contacts) Lifespan, mechanical (control contacts) 0 c (contacts) Voltage type AC ETIM for 248261 Modular devices for distribution board/surface mounting (EC001655)

Feature Name

Feature Value

Rated voltage (EF000228)

250 V

Rated current I_u (EF003981)

15 A

Just-operate current (EF004382)

15 A

Max. time-delayed switch-off (EF004921)

0 ms

Max. continuous current (EF004941)

32 A

Number of contacts as normally open contact (EF008256)

1

Number of contacts as normally closed contact (EF008255)

0....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-LAR32-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.