

INDUSTRIAL COMPONENT DATA

NZM3-XR110-130AC 259848 Y7-259848 EATON ELECTRIC

Remote operator, 110-130VAC, for size 3

Brand: EATON - MOELLER | Manufacturer Part Number: NZM3-XR110-130AC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM3-XR110-130AC
Catalog number	Y7-259848
Category	Motor operator for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-F1B6B10A75
Generated	2026-08-05

Product Overview

Remote operator, 110-130VAC, for size 3

NZM3-XR110-130AC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Remote operator, 110-130VAC, for size 3

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: for remote switching of circuit-breakers and switch-disconnectors. ON and OFF switching and resetting by means of two-wire or three-wire control. Local switching by hand possible. lockable in the 0 position of the remote operator with up to 3 padlocks (hasp thickness: 4-8mm). Can be synchronized. Cannot be combined with mechanical interlock. Cannot be combined with dual auxiliary switch M22-CK11 . Can be used for: NZM3(-4), N(N/O)3(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM remote operator Catalog Number 259848 Model Code NZM3-XR110-130AC EAN 4015082598488 Product Length/Depth 170 mm Product Height 140 mm Product Width 140 mm Product Weight 3.139 kg

Compliances IEC

UL/CSA

RoHS conform Certifications CSA (File No. 22086)

UL (Category Control Number DIHS)

CE marking

UL listed

IEC60947

CSA-C22.2 No. 5-09

CSA (Class No. 1437-01)

CSA certified

UL489

UL (File No. E140305) Product specifications

Type Special features Cannot be combined with switch-disconnector PN...

M22-CK11(20/02) dual auxiliary switch cannot be combined with NZM3-XR... remote operator

Voltage rating 110 - 130 V 50/60 Hz 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requireme...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM3-XR110-130AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.