

INDUSTRIAL COMPONENT DATA

NZM3-XR208-240AC 259850 Y7-259850 EATON ELECTRIC Remote operator, 208-240VAC, for size 3

Brand: EATON - MOELLER | Manufacturer Part Number: NZM3-XR208-240AC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM3-XR208-240AC
Catalog number	Y7-259850
Category	Motor operator for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-4D53E6ADB0
Generated	2026-08-04

Product Overview

Remote operator, 208-240VAC, for size 3

NZM3-XR208-240AC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Remote operator, 208-240VAC, for size 3

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: for remote switching of circuit-breakers and switch-disconnectors. ON and OFF switching and resetting by means of two-wire or three-wire control. Local switching by hand possible. lockable in the 0 position of the remote operator with up to 3 padlocks (hasp thickness: 4-8mm). Can be synchronized. Cannot be combined with mechanical interlock. Cannot be combined with dual auxiliary switch M22-CK11 . Can be used for: NZM3(-4), N(N/O)3(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM remote operator Catalog Number 259850 Model Code NZM3-XR208-240AC EAN 4015082598501 Product Length/Depth 170 mm Product Height 140 mm Product Width 140 mm Product Weight 3.155 kg

Compliances UL/CSA

IEC

RoHS conform Certifications CSA (File No. 22086)

CE marking

CSA (Class No. 1437-01)

UL (File No. E140305)

UL489

IEC60947

UL listed

CSA certified

CSA-C22.2 No. 5-09

UL (Category Control Number DIHS) Product specifications

Type Special features Cannot be combined with switch-disconnector PN...

M22-CK11(20/02) dual auxiliary switch cannot be combined with NZM3-XR... remote operator

Voltage rating 208 - 240 V 50/60 Hz 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requireme...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM3-XR208-240AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.