

INDUSTRIAL COMPONENT DATA

NZM2-XRD208-240AC 115391 Y7-115391 EATON ELECTRIC

Remote operator, 208-240VAC, standard

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2-XRD208-240AC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2-XRD208-240AC
Catalog number	Y7-115391
Category	Motor operator for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-F1FD5FCCFD
Generated	2026-08-03

Product Overview

Remote operator, 208-240VAC, standard

NZM2-XRD208-240AC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Remote operator, 208-240VAC, standard

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: for remote switching of circuit-breakers and switch-disconnectors. ON and OFF switching and resetting by means of two-wire or three-wire control. Local switching by hand possible. lockable in the 0 position of the remote operator with up to 3 padlocks (hasp thickness: 4-8mm). Sliding switch for Auto or Manual. Max. number auxiliary contacts: 2 standard auxiliary contacts , 1 trip-indicating auxiliary switches Cannot be combined with switch-disconnector PN.. Cannot be combined with mechanical interlock. Can be used for: NZM2(-4) , N(N/O)2(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM remote operator Catalog Number 115391 Model Code NZM2-XRD208-240AC
EAN 4015081151233 Product Length/Depth 150 mm Product Height 105 mm Product Width 105 mm Product Weight 1.25
kg Compliances CE Marked
UL/CSA
IEC

RoHS conform Certifications IEC 60947

UL 489

UL listed

CSA-C22.2 No. 5-09

CE marking

CSA (File No. 22086)

UL489

CSA certified

UL (Category Control Number DIHS)

CSA (Class No. 1437-01)

UL (File No. E140305) Product specifications

Type Special features Sliding switch for "Auto" or "Manual"

Max. number auxiliary contacts: 2 standard auxiliary contacts, 1 trip-indicating auxiliary switches

Cannot be combined with switch-disconnector PN...

Cannot be combined with mechanical interlock

Do not install M22-CK11(20/02) dual auxiliary contacts in the center auxiliary contact slot in NZM2-XRD

Voltage rating 208 - 240 V 50/60 Hz 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requireme...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2-XRD208-240AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.