

INDUSTRIAL COMPONENT DATA

NZM4-XR24-30DC 266691 Y7-266691 EATON ELECTRIC

Remote operator, 24-30VAC, for size 4

Brand: EATON - MOELLER | Manufacturer Part Number: NZM4-XR24-30DC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM4-XR24-30DC
Catalog number	Y7-266691
Category	Motor operator for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-33C2426F96
Generated	2026-08-04

Product Overview

Remote operator, 24-30VAC, for size 4

NZM4-XR24-30DC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Remote operator, 24-30VAC, for size 4

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: for remote switching of circuit-breakers and switch-disconnectors. ON and OFF switching and resetting by means of two-wire or three-wire control. Local switching by hand possible. lockable in the 0 position of the remote operator with up to 3 padlocks (hasp thickness: 4-8mm). Can be synchronized. Cannot be combined with mechanical interlock. Can be used for: NZM4(-4), N(N/O)4(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM remote operator Catalog Number 266691 Model Code NZM4-XR24-30DC EAN 4015082666910 Product Length/Depth 189 mm Product Height 202 mm Product Width 210 mm Product Weight 6.354 kg

Compliances IEC

UL/CSA

RoHS conform Certifications UL489

CSA (Class No. 1437-01)

UL (Category Control Number DIHS)

CE marking

CSA certified

UL (File No. E140305)

CSA-C22.2 No. 5-09

UL listed

IEC60947

CSA (File No. 22086) Product specifications

Used with N(S)4(-4)

NZM4(-4) Type Special features Cannot be combined with switch-disconnector PN...

Do not install M22-CK11(20/02) dual auxiliary contacts in the right-hand side auxiliary contact slot in NZM4-XR

Voltage rating 24 - 30 V DC 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation.

Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2

Verification of resistance of insulating materials to normal...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM4-XR24-30DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.