

INDUSTRIAL COMPONENT DATA

NZM3-XR48-60DC 259856 Y7-259856 EATON ELECTRIC

Remote operator, 48-60VDC, for size 3

Brand: EATON - MOELLER | Manufacturer Part Number: NZM3-XR48-60DC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM3-XR48-60DC
Catalog number	Y7-259856
Category	Motor operator for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-00BD745D7A
Generated	2026-08-04

Product Overview

Remote operator, 48-60VDC, for size 3

NZM3-XR48-60DC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Remote operator, 48-60VDC, for size 3

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: for remote switching of circuit-breakers and switch-disconnectors. ON and OFF switching and resetting by means of two-wire or three-wire control. Local switching by hand possible. lockable in the 0 position of the remote operator with up to 3 padlocks (hasp thickness: 4-8mm). Can be synchronized. Cannot be combined with mechanical interlock. Cannot be combined with dual auxiliary switch M22-CK11 . Can be used for: NZM3(-4), N3(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM remote operator Catalog Number 259856 Model Code NZM3-XR48-60DC EAN 4015082598563 Product Length/Depth 170 mm Product Height 140 mm Product Width 140 mm Product Weight 2.8 kg

Compliances UL/CSA

IEC

RoHS conform Certifications UL listed

CSA (Class No. 1437-01)

CSA (File No. 22086)

CSA-C22.2 No. 5-09

CSA certified

UL (Category Control Number DIHS)

IEC60947

UL489

UL (File No. E140305)

CE marking Product specifications

Type Accessory Remote operator, can be synchronized Special features Cannot be combined with switch-disconnector PN...M22-CK11(20/02) dual auxiliary switch cannot be combined with NZM3-XR... remote operator Voltage rating 48 - 60 V DC 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM3-XR48-60DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.