

INDUSTRIAL COMPONENT DATA

Z-FAM 248293 Y7-248293 EATON ELECTRIC Remote tripping module, for PFIM, PFHM-4p, dRCM

Brand: EATON - MOELLER | Manufacturer Part Number: Z-FAM



Manufacturer	EATON - MOELLER
MPN / Reference	Z-FAM
Catalog number	Y7-248293
Category	Auxiliary device for distribution board devices
Minimum order	4 Pcs
Document ID	EO-BEA8AAB087
Generated	2026-08-05

Product Overview

Remote tripping module, for PFIM, PFHM-4p, dRCM

Z-FAM

Eaton Distribution parts. Remote tripping module, for PFIM, PFHM-4p, dRCM

For remotely switching off residual current circuit-breakers, miniature circuit breaker/DI and RCBO combination switches, remote de-energization with one or more parallel dry contacts, e.g. button with max. 3 A rated operation current at 250 V, observe max. pushbutton voltage, remote trip testing with Z-FW remote testing module, can be retrofitted and wired to the appropriate residual current circuit-breaker terminals as specified in the circuit diagram, trip module for PFIM 0.5A please enquire, no dangerous accidental energization of consumer system during remote de-energization process, ensured with integrated K1-K2 contact breaker

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 248293 Model Code Z-FAM EAN 4015082482930 Product Length/Depth 80 mm Product Height 66 mm Product Width 9 mm Product Weight 0.05 kg Compliances RoHS conform Certifications EN45545-2

IEC 61373 Product specifications

Type Application Switchgear for industrial and advanced commercial applications Accessory/spare part type Residual current release module Used with Trip module

Accessory for residual current circuit breaker

Accessory Mounting method For fitting on left to: FI Additional equipment required Remote release Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 0.5 TE Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 0 Number of switches (fault signal) 0 Voltage type AC Functions Remote drive Device fitting Earth leakage switch Rated operational voltage (Ue) - max 400 V Rated switch current 0 A Suitable for current of main contact unit - max 0 A

ETIM for 248293 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Device fitting (EF007826)

Earth leakage switch

Width in number of modular spacings (EF002950)

0.5

Number of contacts as normally open contact (EF008256)

1

Number of contacts as normally closed contact (EF008255)

0

Number of contacts as change-over contact (EF008257)

0

Numb...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-FAM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.