

INDUSTRIAL COMPONENT DATA

Z-KAM 248294 Y7-248294 EATON ELECTRIC Remote tripping module, for PKNM, PKDM, PFHM-2p

Brand: EATON - MOELLER | Manufacturer Part Number: Z-KAM



Manufacturer	EATON - MOELLER
MPN / Reference	Z-KAM
Catalog number	Y7-248294
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-DEEA543517
Generated	2026-08-03

Product Overview

Remote tripping module, for PKNM, PKDM, PFHM-2p

Z-KAM

For remotely switching off residual current circuit-breakers, miniature circuit breaker/DI and RCBO combination switches, remote de-energization with one or more parallel dry contacts, e.g. button with max. 3 A rated operation current at 250 V, observe max. pushbutton voltage, remote trip testing with Z-FW remote testing module, can be retrofitted and wired to the appropriate residual current circuit-breaker terminals as specified in the circuit diagram, trip module for PFIM 0.5A please enquire, no dangerous accidental energization of consumer system during remote de-energization process, ensured with integrated K1-K2 contact breaker

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Remote tripping module, for PKNM, PKDM, PFHM-2pFor remotely switching off residual current circuit-breakers, miniature circuit breaker/DI and RCBO combination switches, remote de-energization with one or more parallel dry contacts, e.g. button with max. 3 A rated operation current at 250 V, observe max. pushbutton voltage, remote trip testing with Z-FW remote testing module, can be retrofitted and wired to the appropriate residual current circuit-breaker terminals as specified in the circuit diagram, trip module for PFIM 0.5A please enquire, no dangerous accidental energization of consumer system during remote de-energization process, ensured with integrated K1-K2 contact breaker

General specificationsProduct nameEaton Distribution partsPart no.Z-KAMEAN4015082482947Product Length/Depth80 millimetreProduct height66 millimetreProduct width9 millimetreProduct weight0.05 kilogramCompliancesRoHS

conformCertificationsEN45545-2

IEC 61373Product TradenameNoneProduct TypeDistribution partsProduct Sub TypeNonePublic ConsumptionYesProduct Family DescriptionES-PMCC-PDC-Eaton Distribution partsGlobally MarketableYesProduct Specification DetailsAccessory/spare part typeResidual current release moduleAdditional equipment requiredRemote releaseAmbient operating temperature - max40 °CAmbient operating temperature - min-5 °CAppliationSwitchgear for industrial and advanced commercial applicationsAssembly width0.5Device fittingOtherNumber of contacts (change-over contacts)0Number of contacts (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-KAM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.