

INDUSTRIAL COMPONENT DATA

DILM150-XSP(RAC24) 230109 Y7-230109 EATON ELECTRIC

Replacement coil alternating current for DILM115-150

Brand: EATON - MOELLER | Manufacturer Part Number: DILM150-XSP(RAC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM150-XSP(RAC24)
Catalog number	Y7-230109
Category	Coil for relay
Minimum order	1 Pcs
Document ID	EO-2D223B4B7A
Generated	2026-08-05

Product Overview

Replacement coil alternating current for DILM115-150

DILM150-XSP(RAC24)

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RAC 24: 24 V 50/60 Hz, AC, For use with: DILM115, DILM150, DILM170, DILMP125 - DILMP200

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: RAC 24: 24 V 50/60 Hz, Voltage AC/DC: AC, For use with: DILM115, DILM150, DILM170, DILMP125 - DILMP200, DILM115 - DILM170 (incl. electronic module)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM replacement coil Catalog Number 230109 Model Code DILM150-XSP(RAC24)

EAN 4015082301095 Product Length/Depth 51 mm Product Height 110 mm Product Width 63.2 mm Product Weight 0.245

kg Certifications UL 508

IEC/EN 60947-4-1

CE

CSA-C22.2 No. 14-05

CSA File No.: 012528

UL File No.: E29096

UL

UL Category Control No.: NLDX

CSA

CSA Class No.: 2411-03, 3211-04 General

Accessories Individual coils Product category Accessories Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 24 V Rated control supply voltage (Us) at AC, 50 Hz - max 24 V Rated

control supply voltage (Us) at AC, 60 Hz - min 24 V Rated control supply voltage (Us) at AC, 60 Hz - max 24 V Rated

control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Design verification

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of

enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal

heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect.

effects Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be

evaluated. 10.2.6 Mechanical im...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM150-XSP(RAC24) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.