

INDUSTRIAL COMPONENT DATA

DILM150-XSP(RAC120) 230111 Y7-230111 EATON ELECTRIC

Replacement coil alternating current for DILM115-150

Brand: EATON - MOELLER | Manufacturer Part Number: DILM150-XSP(RAC120)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM150-XSP(RAC120)
Catalog number	Y7-230111
Category	Coil for relay
Minimum order	1 Pcs
Document ID	EO-F750BD87F9
Generated	2026-08-03

Product Overview

Replacement coil alternating current for DILM115-150

DILM150-XSP(RAC120)

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RAC 120: 100 - 120 V 50/60 Hz, AC, For use with: DILM115, DILM150, DILM170, DILMP125 - DILMP200

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: RAC 120: 100 - 120 V 50/60 Hz, Voltage AC/DC: AC, For use with: DILM115, DILM150, DILM170, DILMP125 - DILMP200, DILM115 - DILM170 (incl. electronic module)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM replacement coil Catalog Number 230111 Model Code DILM150-XSP(RAC120)

EAN 4015082301118 Product Length/Depth 51 mm Product Height 110 mm Product Width 63.2 mm Product Weight 0.245

kg Certifications CSA-C22.2 No. 14-05

CSA

UL Category Control No.: NLDX

CE

CSA File No.: 012528

UL

CSA Class No.: 2411-03, 3211-04

IEC/EN 60947-4-1

UL 508

UL File No.: E29096 General

Accessories Individual coils Product category Accessories Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 100 V Rated control supply voltage (Us) at AC, 50 Hz - max 120 V

Rated control supply voltage (Us) at AC, 60 Hz - min 100 V Rated control supply voltage (Us) at AC, 60 Hz - max 120 V

Rated control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Design verification

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of

enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal

heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect.

effects Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be

evaluated. 10.2.6 Mechanic...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM150-XSP(RAC120) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.