

INDUSTRIAL COMPONENT DATA

DILM150-XSP(RAC440) 230113 Y7-230113 EATON ELECTRIC

Replacement coil alternating current for DILM115-150

Brand: EATON - MOELLER | Manufacturer Part Number: DILM150-XSP(RAC440)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM150-XSP(RAC440)
Catalog number	Y7-230113
Category	Coil for relay
Minimum order	1 Pcs
Document ID	EO-26B38DB28E
Generated	2026-08-04

Product Overview

Replacement coil alternating current for DILM115-150

DILM150-XSP(RAC440)

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RAC 440: 380 - 440 V 50/60 Hz, AC, For use with: DILM115, DILM150, DILM170

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: RAC 440: 380 - 440 V 50/60 Hz, Voltage AC/DC: AC, For use with: DILM115, DILM150, DILM170, DILM115 - DILM170 (incl. electronic module)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM replacement coil Catalog Number 230113 Model Code DILM150-XSP(RAC440)

EAN 4015082301132 Product Length/Depth 51 mm Product Height 110 mm Product Width 63.2 mm Product Weight 0.245

kg Certifications UL

CE

CSA File No.: 012528

UL 508

CSA-C22.2 No. 14-05

CSA Class No.: 2411-03, 3211-04

UL File No.: E29096

IEC/EN 60947-4-1

CSA

UL Category Control No.: NLDX General

Accessories Individual coils Product category Accessories Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 380 V Rated control supply voltage (Us) at AC, 50 Hz - max 440 V

Rated control supply voltage (Us) at AC, 60 Hz - min 380 V Rated control supply voltage (Us) at AC, 60 Hz - max 440 V

Rated control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Design verification

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of

enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal

heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect.

effects Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2.6 Mechanic...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM150-XSP(RAC440) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.