

INDUSTRIAL COMPONENT DATA

DILM32-XSP(*V50HZ) 281153 EATON ELECTRIC Replacement coil alternating current for DILM17-32

Brand: EATON - MOELLER | Manufacturer Part Number: DILM32-XSP(*V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM32-XSP(*V50HZ)
Catalog number	-
Category	Coil for relay
Minimum order	10 Pcs
Document ID	EO-CADBF68202
Generated	2026-08-04

Product Overview

Replacement coil alternating current for DILM17-32

Spare coil; For DILM17 contactors... 38; * V 50 Hz

Replacement coil, Tool-less plug connection, ...V 50 Hz, AC, For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45, Minimum order quantity 10 items (packaging unit)

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: ...V 50 Hz, Voltage AC/DC: AC, For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45, DILM17 - DILM38

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > KDIL Accessories
--------------	------------------------------------

Additional Product Information

Replacement coil, Tool-less plug connection, ...V 50 Hz, AC, For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45, Minimum order quantity 10 items (packaging unit)Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: ...V 50 Hz, Voltage AC/DC: AC, For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45, DILM17 - DILM38Delivery program

Actuating voltage...V 50 HzVoltage AC/DCACFor use withDILM17

DILM25

DILM32

DILM38

DILMP32 - DILMP45For use withDILM17 - DILM38Note on equipment suppliedMinimum order quantity 10 items (packaging unit)Design verification as per IEC/EN 61439

Operating ambient temperature min. -25 °C Operating ambient temperature max. +60 °C Technical data ETIM 7.0
Low-voltage industrial components (EG000017) / Coil for relay (EC001043) Electric engineering, automation, process
control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor ()
[AKF021013]) Rated control supply voltage U_s at AC 50 Hz 12 - 600 V Rated control supply voltage U_s at AC 60 Hz 0 - 0
V Rated control supply voltage U_s at DC 0 - 0 V Voltage type for actuating AC Approvals
Product Standards IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking UL File No. E29096 UL Category Control
No. NLDX CSA File No. 012528 CSA Class No. 2411-03, 3211-04 North America Certification UL listed, CSA certified Specially
designed for North America No
ETIM for 281153 Low-voltage industrial controls and switchgear (EC001043)
Feature Name
Feature Value...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM32-XSP(*V50HZ) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.