


INDUSTRIAL COMPONENT DATA

DILM32-XSP(*V60HZ) 281154 EATON ELECTRIC Replacement coil alternating current for DILM17-32

Brand: EATON - MOELLER | Manufacturer Part Number: DILM32-XSP(*V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM32-XSP(*V60HZ)
Catalog number	-
Category	Coil for relay
Minimum order	10 Pcs
Document ID	EO-2A248C5EE9
Generated	2026-08-04

Product Overview

Replacement coil alternating current for DILM17-32

Spare coil; For DILM17 contactors... 38; * V 60 Hz

Replacement coil, Tool-less plug connection, ...V 60 Hz, AC, For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45, Minimum order quantity 10 items (packaging unit)

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: ...V 60 Hz, Voltage AC/DC: AC, For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45, DILM17 - DILM38

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > KDIL Accessories
--------------	------------------------------------

Additional Product Information

Replacement coil, Tool-less plug connection, ...V 60 Hz, AC, For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45, Minimum order quantity 10 items (packaging unit)Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: ...V 60 Hz, Voltage AC/DC: AC, For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45, DILM17 - DILM38Delivery program

Actuating voltage...V 60 HzVoltage AC/DCACFor use withDILM17

DILM25

DILM32

DILM38

DILMP32 - DILMP45For use withDILM17 - DILM38Note on equipment suppliedMinimum order quantity 10 items (packaging unit)Design verification as per IEC/EN 61439

Operating ambient temperature min.-25 °COperating ambient temperature max.+60 °CTechnical data ETIM 7.0
Low-voltage industrial components (EG000017) / Coil for relay (EC001043)Electric engineering, automation, process
control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (
[AKF021013])Rated control supply voltage Us at AC 50HZ0 - 0 VRated control supply voltage Us at AC 60HZ12 - 600
VRated control supply voltage Us at DC0 - 0 VVoltage type for actuatingACAApprovals
Product StandardsIEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE markingUL File No.E29096UL Category Control
No.NLDXCSA File No.012528CSA Class No.2411-03, 3211-04North America CertificationUL listed, CSA certifiedSpecially
designed for North AmericaNo
ETIM for 281154 Low-voltage industrial controls and switchgear (EC001043)
Feature Name
Feature Value...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM32-XSP(*V60HZ) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.