

INDUSTRIAL COMPONENT DATA

DILM65-XSP(190V50HZ,220V60HZ) 281169 Y7-281169 EATON ELECTRIC Replacement coil alternating current for DILM4..

Brand: EATON - MOELLER | Manufacturer Part Number: DILM65-XSP(190V50HZ,220V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM65-XSP(190V50HZ,220V60HZ)
Catalog number	Y7-281169
Category	Coil for relay
Minimum order	1 Pcs
Document ID	EO-7E393F2C20
Generated	2026-08-06

Product Overview

Replacement coil alternating current for DILM40-65

DILM65-XSP(190V50HZ,220V60HZ)

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, 190 V 50 Hz, 220 V 60 Hz, AC, For use with: DILM40, DILM50, DILM65, DILM72

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: 190 V 50 Hz, 220 V 60 Hz, Voltage AC/DC: AC, For use with: DILM40, DILM50, DILM65, DILM72, DILM40 - DILM72

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM replacement coil Catalog Number 281169 Model Code

DILM65-XSP(190V50HZ,220V60HZ) EAN 4015082811693 Product Length/Depth 69 mm Product Height 48 mm Product Width 56 mm Product Weight 0.071 kg Certifications CSA Class No.: 2411-03, 3211-04

CE

CSA File No.: 012528

IEC/EN 60947-4-1

UL

UL 508

UL Category Control No.: NLDX

CSA

UL File No.: E29096

CSA-C22.2 No. 14-05 General

Accessories Individual coils Product category Accessories Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 190 V Rated control supply voltage (Us) at AC, 50 Hz - max 190 V

Rated control supply voltage (Us) at AC, 60 Hz - min 220 V Rated control supply voltage (Us) at AC, 60 Hz - max 220 V

Rated control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Design verification

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of

enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal

heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect.

effects Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2.6 M...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM65-XSP(190V50HZ,220V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.