

INDUSTRIAL COMPONENT DATA

DILM65-XSP(*V60HZ) 281184 EATON ELECTRIC Replacement coil alternating current for DILM40-65

Brand: EATON - MOELLER | Manufacturer Part Number: DILM65-XSP(*V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM65-XSP(*V60HZ)
Catalog number	-
Category	Coil for relay
Minimum order	5 Pcs
Document ID	EO-62C4EC60A6
Generated	2026-08-02

Product Overview

Replacement coil alternating current for DILM40-65

Replacement Coil For DILM40 Contactors... 72*V 60Hz

Replacement coil, Tool-less plug connection, ...V 60 Hz, AC, For use with: DILM40, DILM50, DILM65, DILM72, DILMP63, DILMP80, Minimum order quantity 5 items (packaging unit)

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: ...V 60 Hz, Voltage AC/DC: AC, For use with: DILM40, DILM50, DILM65, DILM72, DILMP63, DILMP80, DILM40 - DILM72

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > KDIL Accessories
--------------	------------------------------------

Additional Product Information

Replacement coil, Tool-less plug connection, ...V 60 Hz, AC, For use with: DILM40, DILM50, DILM65, DILM72, DILMP63, DILMP80, Minimum order quantity 5 items (packaging unit)Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: ...V 60 Hz, Voltage AC/DC: AC, For use with: DILM40, DILM50, DILM65, DILM72, DILMP63, DILMP80, DILM40 - DILM72Delivery program

Actuating voltage...V 60 HzVoltage AC/DCACFor use withDILM40

DILM50

DILM65

DILM72

DILMP63

DILMP80For use withDILM40 - DILM72Note on equipment suppliedMinimum order quantity 5 items (packaging unit)Design

verification as per IEC/EN 61439

Operating ambient temperature min. -25 °C Operating ambient temperature max. +60 °C Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043) Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor ()

[AKF021013]) Rated control supply voltage U_s at AC 50 Hz 0 - 0 V Rated control supply voltage U_s at AC 60 Hz 12 - 600

V Rated control supply voltage U_s at DC 0 - 0 V Voltage type for actuating AC Approvals

Product Standards IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking UL File No. E29096 UL Category Control No. NLDX CSA File No. 012528 CSA Class No. 2411-03, 3211-04 North America Certification UL listed, CSA certified Specially designed for North America No

ETIM for 281184 Low-voltage industrial controls and switchgear (EC001043)

Feature Name

Feature Value

Rated...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM65-XSP(*V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.