

INDUSTRIAL COMPONENT DATA

PFDM-125/4/01-A 235921 XTMCXFA13 EATON ELECTRIC

Residual current circuit breaker (RCCB), 125A, 4p, 100mA, ty..

Brand: EATON - MOELLER | Manufacturer Part Number: PFDM-125/4/01-A



Manufacturer	EATON - MOELLER
MPN / Reference	PFDM-125/4/01-A
Catalog number	XTMCXFA13
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-0B083F1914
Generated	2026-08-05

Product Overview

Residual current circuit breaker (RCCB), 125A, 4p, 100mA, type A

Modern residual current circuit-breaker for rated 125 A current range, for fault and additional protection, Auxiliary contact, selective part no. Suitable for use in the free (on-site power and outdoor distribution board) to -25 °C, mains-voltage-independent tripping, can be used for people and additional protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Auxiliary contact, 1N/O+3N/C, surface mounting, screw connection Alternate Catalog No. XTMCXFA13 EL-Nummer (Norway) 4110170 Auxiliary contact module, with interlocked opposing contacts, Switching elements according to EN 50005, Switching elements according to EN 50012 are to be preferred., Version E combinations correspond to EN 50011 and are to be preferred., Function: for standard applications, 4 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 2 A, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 3 NC, Mounting type: Front fixing, For use with: DILEM-10(-G)(...), DILEM-01(-G)(...), DILEM-4(-G)(...), DILER40(-G), DILER31(-G), DILER22, DILEEM-10(-G)(...), DILEEM-01(-G)(...), DILEM12-10(-G)(...), DILEM12-01(-G)(...), Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 appendix L, inside the auxiliary contact modules, also for the integrated auxiliary contacts of the DILE(E)M, Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open), Code number and version of combination Distinctive number: 53E, 44, 35 [Delivery program Accessories Auxiliary contact modules Description with interlocked opposing contacts

Switching elements according to EN 50005

Switching elements according to EN 50012 are to be preferred.

Version E combinations correspond to EN 50011 and are to be preferred. Function for stan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PFDM-125/4/01-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.