

## INDUSTRIAL COMPONENT DATA

**PFIM-25/2/05-MW 235393 Y7-235393 EATON ELECTRIC  
Residual current circuit breaker (RCCB), 25A, 2p, 500mA, typ..**

Brand: EATON - MOELLER | Manufacturer Part Number: PFIM-25/2/05-MW



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | EATON - MOELLER                         |
| MPN / Reference | PFIM-25/2/05-MW                         |
| Catalog number  | Y7-235393                               |
| Category        | Residual current circuit breaker (RCCB) |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-A69374BCE3                           |
| Generated       | 2026-08-05                              |

**Product Overview**

Residual current circuit breaker (RCCB), 25A, 2p, 500mA, type AC

PFIM-25/2/05-MW

Residual current circuit-breaker PFIM, 2 pole, Rated current In: 25 A, Rated short-circuit strength Icn: 10 kA, Rated fault current I?N: 0.5 A, Type AC, AC current sensitive, Partly surge-proof 250 A, Switchgear for residential and commercial applications

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |                                                                  |
|--------------|------------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Modular Switchgear - Tertiary and Differential |
|--------------|------------------------------------------------------------------|

**Additional Product Information**

Residual current circuit breaker (RCCB), 25A, 2p, 500mA, type ACResidual current circuit-breaker PFIM, 2 pole, Rated current In: 25 A, Rated short-circuit strength Icn: 10 kA, Rated fault current I?N: 0.5 A, Type AC, AC current sensitive, Partly surge-proof 250 A, Switchgear for residential and commercial applications

General specificationsProduct nameEaton Moeller series xPole - PFIM Type AC, A, U, R RCCBPart

no.PFIM-25/2/05-MWEAN4015082353933Product Length/Depth80 millimetreProduct height76 millimetreProduct width35 millimetreProduct weight0.181 kilogramCompliancesRoHS conformCertificationsIEC/EN 61008Product TradenamexPole - PFIM Type AC, A, U, RProduct TypeRCCBProduct Sub TypeNoneDelivery programApplicationResidual current circuit breaker for residential and commercial applications

xPole - Switchgear for residential and commercial applicationsNumber of polesTwo-poleTripping

timeNon-delayedAmperage Rating25 ARated short-circuit strength10 kAFault current rating500 mASensitivity typeAC current sensitiveImpulse withstand currentPartly surge-proof 250 ATypePFIM

## Residual current circuit breakers

Type AC  
Technical Data - Electrical  
Voltage rating 230 V AC  
Rated operational voltage (U<sub>e</sub>) - max 230 V  
Rated insulation voltage (U<sub>i</sub>) 440 V  
Rated impulse withstand voltage (U<sub>imp</sub>) 4 kV  
Rated fault current - min 0.5 A  
Rated fault current - max 0.5 A  
Frequency rating 50 Hz  
Short-circuit rating 63 A (max. admissible back-up fuse)  
Leakage current type AC  
Rated residual making and breaking capacity 500 A  
Admissib...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PFIM-25/2/05-MW with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

## GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.