

INDUSTRIAL COMPONENT DATA

PFIM-25/2/05-MW 235393 Y7-235393 EATON ELECTRIC Residual current circuit breaker (RCCB), 25A, 2p, 500mA, typ..

Brand: EATON - MOELLER | Manufacturer Part Number: PFIM-25/2/05-MW



Manufacturer	EATON - MOELLER
MPN / Reference	PFIM-25/2/05-MW
Catalog number	Y7-235393
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-A69374BCE3
Generated	2026-08-06

Product Overview

Residual current circuit breaker (RCCB), 25A, 2p, 500mA, type AC

PFIM-25/2/05-MW

Residual current circuit-breaker PFIM, 2 pole, Rated current In: 25 A, Rated short-circuit strength Icn: 10 kA, Rated fault current I?N: 0.5 A, Type AC, AC current sensitive, Partly surge-proof 250 A, Switchgear for residential and commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Tertiary and Differential
--------------	--

Additional Product Information

Residual current circuit breaker (RCCB), 25A, 2p, 500mA, type ACResidual current circuit-breaker PFIM, 2 pole, Rated current In: 25 A, Rated short-circuit strength Icn: 10 kA, Rated fault current I?N: 0.5 A, Type AC, AC current sensitive, Partly surge-proof 250 A, Switchgear for residential and commercial applications

General specificationsProduct nameEaton Moeller series xPole - PFIM Type AC, A, U, R RCCBPart

no.PFIM-25/2/05-MWEAN4015082353933Product Length/Depth80 millimetreProduct height76 millimetreProduct width35 millimetreProduct weight0.181 kilogramCompliancesRoHS conformCertificationsIEC/EN 61008Product TradenamexPole - PFIM Type AC, A, U, RProduct TypeRCCBProduct Sub TypeNoneDelivery programApplicationResidual current circuit breaker for residential and commercial applications

xPole - Switchgear for residential and commercial applicationsNumber of polesTwo-poleTripping

timeNon-delayedAmperage Rating25 ARated short-circuit strength10 kAFault current rating500 mASensitivity typeAC current sensitiveImpulse withstand currentPartly surge-proof 250 ATypePFIM

Residual current circuit breakers

Type ACTechnical Data - ElectricalVoltage rating230 V ACRated operational voltage (Ue) - max230 VRated insulation voltage (Ui)440 VRated impulse withstand voltage (Uimp)4 kVRated fault current - min0.5 ARated fault current - max0.5 AFrequency rating50 HzShort-circuit rating63 A (max. admissible back-up fuse)Leakage current typeACRated residual making and breaking capacity500 AAdmissib...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PFIM-25/2/05-MW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.