

INDUSTRIAL COMPONENT DATA

PFIM-40/2/03-MW 235396 Y7-235396 EATON ELECTRIC
Residual current circuit breaker (RCCB), 40A, 2p, 300mA, typ..

Brand: EATON - MOELLER | Manufacturer Part Number: PFIM-40/2/03-MW



Manufacturer	EATON - MOELLER
MPN / Reference	PFIM-40/2/03-MW
Catalog number	Y7-235396
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-BBC164B4C4
Generated	2026-08-06

Product Overview

Residual current circuit breaker (RCCB), 40A, 2p, 300mA, type AC

PFIM-40/2/03-MW

Eaton Moeller series xPole - PFIM Type AC, A, U, R RCCB. PFIM, 2 pole, In: 40 A, Icn: 10 kA, I?N: 0.3 A, Type AC, AC current sensitive, Partly surge-proof 250 A, residential and commercial

Residual current circuit-breaker PFIM, 2 pole, Rated current In: 40 A, Rated short-circuit strength Icn: 10 kA, Rated fault current I?N: 0.3 A, Type AC, AC current sensitive, Partly surge-proof 250 A, Switchgear for residential and commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Differential

Additional Product Information

General specifications

Product Name Eaton Moeller series xPole - PFIM Type AC, A, U, R RCCB

Catalog Number 235396

Model Code PFIM-40/2/03-MW

EAN 4015082353964

Product Length/Depth 76 mm

Product Height 80 mm

Product Width 35 mm

Product Weight 0.181 kg

Compliances RoHS conform
Certifications IEC/EN 61008
Delivery program
Application Residual current circuit breaker for residential and commercial applications
xPole - Switchgear for residential and commercial applications
Number of poles Two-pole
Tripping time Non-delayed
Amperage Rating 40 A
Rated short-circuit strength 10 kA
Fault current rating 300 mA
Sensitivity type AC current sensitive
Impulse withstand current Partly surge-proof 250 A
Type PFIM
Residual current circuit breakers
Type AC
Technical Data - Electrical
Voltage rating 230 V AC
Rated operational voltage (Ue) - max 230 V
Rated insulation voltage (Ui) 440 V
Rated impulse withstand voltage (Uimp) 4 kV
Rated fault current - min 0.3 A
Rated fault current - max 0.3 A
Frequency rating 50 Hz
Short-circuit rating 63 A (max. admissible back-up fuse)
Leakage current type AC
Rated residual making and breaking capacity 500 A
Admissible back-up fuse overload - max 25 A gG/gL
Rated short-time withstand current (Icw) 10 kA
Surge current capacity 0.25 kA
Test circuit range 196 V AC - 264 V AC
Pollution degree 2
Lifespan, electrical 4000 operations
Technical Data - Mechanical
Frame 45 mm
Width in number of modular spacings 2
Built-in width (number of units) 35 mm (2 SU)
Built-in d...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PFIM-40/2/03-MW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.