

INDUSTRIAL COMPONENT DATA

PFIM-40/4/05-MW 235413 Y7-235413 EATON ELECTRIC

Residual current circuit breaker (RCCB), 40A, 4p, 500mA, typ..

Brand: EATON - MOELLER | Manufacturer Part Number: PFIM-40/4/05-MW



Manufacturer	EATON - MOELLER
MPN / Reference	PFIM-40/4/05-MW
Catalog number	Y7-235413
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-5A7443D793
Generated	2026-08-05

Product Overview

Residual current circuit breaker (RCCB), 40A, 4p, 500mA, type AC

PFIM-40/4/05-MW

Residual current circuit-breaker PFIM, 4 pole, Rated current In: 40 A, Rated short-circuit strength Icn: 10 kA, Rated fault current I?N: 0.5 A, Switchgear for residential and commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Tertiary and Differential

Additional Product Information

Residual current circuit breaker (RCCB), 40A, 4p, 500mA, type ACResidual current circuit-breaker PFIM, 4 pole, Rated current In: 40 A, Rated short-circuit strength Icn: 10 kA, Rated fault current I?N: 0.5 A, Switchgear for residential and commercial applications

General specificationsProduct nameEaton Moeller series xPole - PFIM Type AC, A, U, R RCCBPart no.PFIM-40/4/05-MWEAN4015082354138Product Length/Depth80 millimetreProduct height76 millimetreProduct width70 millimetreProduct weight0.298 kilogramCompliancesRoHS conformCertificationsIEC/EN 61008Product TradenamexPole - PFIM Type AC, A, U, RProduct TypeRCCBProduct Sub TypeNoneDelivery programApplicationResidual current circuit breaker for residential and commercial applications
xPole - Switchgear for residential and commercial applicationsNumber of polesFour-poleTripping timeNon-delayedAmperage Rating40 ARated short-circuit strength10 kAFault current rating500 mASensitivity typeAC current sensitivelmpulse withstand currentPartly surge-proof 250 ATTypePFIM
Residual current circuit breakers

Type AC
Technical Data - Electrical
Voltage rating 230 V AC / 400 V AC
Rated operational voltage (Ue) - max 400 V
Rated insulation voltage (Ui) 440 V
Rated impulse withstand voltage (Uimp) 4 kV
Rated fault current - min 0.5 A
Rated fault current - max 0.5 A
Frequency rating 50 Hz
Short-circuit rating 63 A (max. admissible back-up fuse)
Leakage current type AC
Rated residual making and breaking capacity 500 A
Admissible back-up fuse overload - max 25 A gG/gL
Rated...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PFIM-40/4/05-MW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.