

## INDUSTRIAL COMPONENT DATA

# PFIM-40/4/05-MW 235413 Y7-235413 EATON ELECTRIC Residual current circuit breaker (RCCB), 40A, 4p, 500mA, typ..

Brand: EATON - MOELLER | Manufacturer Part Number: PFIM-40/4/05-MW



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | EATON - MOELLER                         |
| MPN / Reference | PFIM-40/4/05-MW                         |
| Catalog number  | Y7-235413                               |
| Category        | Residual current circuit breaker (RCCB) |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-5A7443D793                           |
| Generated       | 2026-08-06                              |

## Product Overview

Residual current circuit breaker (RCCB), 40A, 4p, 500mA, type AC

PFIM-40/4/05-MW

Residual current circuit-breaker PFIM, 4 pole, Rated current In: 40 A, Rated short-circuit strength Icn: 10 kA, Rated fault current I?N: 0.5 A, Switchgear for residential and commercial applications

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                  |
|--------------|------------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Modular Switchgear - Tertiary and Differential |
|--------------|------------------------------------------------------------------|

## Additional Product Information

Residual current circuit breaker (RCCB), 40A, 4p, 500mA, type AC  
Residual current circuit-breaker PFIM, 4 pole, Rated current In: 40 A, Rated short-circuit strength Icn: 10 kA, Rated fault current I?N: 0.5 A, Switchgear for residential and commercial applications

General specifications  
Product name Eaton Moeller series xPole - PFIM Type AC, A, U, R RCCB  
Part no. PFIM-40/4/05-MW  
EAN 4015082354138  
Product Length/Depth 80 millimetre  
Product height 76 millimetre  
Product width 70 millimetre  
Product weight 0.298 kilogram  
Compliances RoHS conform  
Certifications IEC/EN 61008  
Product Tradename xPole - PFIM Type AC, A, U, R  
Product Type RCCB  
Product Sub Type None  
Delivery program Application  
Residual current circuit breaker for residential and commercial applications  
xPole - Switchgear for residential and commercial applications  
Number of poles Four-pole  
Tripping time Non-delayed  
Amperage Rating 40 A  
Rated short-circuit strength 10 kA  
Fault current rating 500 mA  
Sensitivity type AC current sensitive  
Impulse withstand current Partly surge-proof 250 A  
Type PFIM  
Residual current circuit breakers

Type ACTechnical Data - ElectricalVoltage rating230 V AC / 400 V ACRated operational voltage (Ue) - max400 VRated insulation voltage (Ui)440 VRated impulse withstand voltage (Uimp)4 kVRated fault current - min0.5 ARated fault current - max0.5 AFrequency rating50 HzShort-circuit rating63 A (max. admissible back-up fuse)Leakage current typeACRated residual making and breaking capacity500 AAdmissible back-up fuse overload - max25 A gG/gLRated...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PFIM-40/4/05-MW with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.