

INDUSTRIAL COMPONENT DATA

Z-FW-LP 248296 Y7-248296 EATON ELECTRIC Restarting device, 220-240VAC, 4HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-FW-LP



Manufacturer	EATON - MOELLER
MPN / Reference	Z-FW-LP
Catalog number	Y7-248296
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-781F9E95F8
Generated	2026-08-04

Product Overview

Restarting device, 220-240VAC, 4HP

Z-FW-LP

Eaton Distribution parts. Restarting device, 220-240VAC, 4HP

Restarting device, operational voltage 220-240V AC, frequency 50/60 Hz, functions: automatic restart, cap installation dimension 45mm, mounting width 4 SU (70mm), top-hat rail mounting, terminal cross-section 2x1.5 mm² or 1x2.5 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 248296 Model Code Z-FW-LP EAN 4015082482961 Product Length/Depth 80 mm Product Height 77.3 mm Product Width 88.4 mm Product Weight 0.298 kg Compliances RoHS conform Product specifications

Type Special features Z-FW... (Test module (0.5 space unit) for remote testing of residual current devices) Application Switchgear for industrial and advanced commercial applications Accessory/spare part type Restarting device Degree of protection IP40 Frame Standard front dimension: 45 mm Frequency rating 50 Hz / 60 Hz Used with Restarting device Accessory for residual current circuit breaker

Accessory

Accessory for miniature circuit breaker Equipment heat dissipation, current-dependent 0 W Mounting method Quick attachment with 2 latch positions on top-hat rail IEC/EN 60715

For fitting on right to: CLS6, PFIM, PFHM-4p, dRCM, Z-A40, PFR, Z-MS Additional equipment required Monitoring unit with automatic reclosing Terminal protection Protection against electric shock to A3, ÖVE-EN 6 Terminal type Lift terminals Ambient operating temperature - max 40 °C Ambient operating temperature - min -25 °C Assembly width 4 TE Enclosure width 80 mm Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 0 Number of poles at main contact unit - max 0 Number of switches (fault s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-FW-LP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.