

INDUSTRIAL COMPONENT DATA

Z-FW-MO 284730 Y7-284730 EATON ELECTRIC Restarting device, 24-240V, 2HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-FW-MO



Manufacturer	EATON - MOELLER
MPN / Reference	Z-FW-MO
Catalog number	Y7-284730
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-7CDCA5924A
Generated	2026-08-03

Product Overview

Restarting device, 24-240V, 2HP

Z-FW-MO

Eaton Distribution parts. Restarting device, 24-240V, 2HP

Remote switching module, control voltage for remote control 24-230V AC relay output for tripping test 400V AC max., functions: automatic restart + ON/OFF/TEST, cap installation dimension 45mm, mounting width 2 SU (35mm), top-hat rail mounting, terminal cross-section 4x1.5 mm² or 2x2.5 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 284730 Model Code Z-FW-MO EAN 4015082847302 Product Length/Depth 80 mm Product Height 65.5 mm Product Width 35 mm Product Weight 0.076 kg Compliances RoHS conform Product specifications

Used with Restarting device - switching module

Accessory for miniature circuit breaker

Accessory

Accessory for residual current circuit breaker Type Special features 24 V AC/DC - 230 V AC/DC (control voltage for remote testing) Application Switchgear for industrial and advanced commercial applications Accessory/spare part type Restarting device Degree of protection IP40 Frame Standard front dimension: 45 mm Equipment heat dissipation, current-dependent 0

W Mounting method Quick attachment with 2 latch positions on top-hat rail IEC/EN 60715

For fitting on right to: Z-FW-LP, Z-FW-LPD Additional equipment required Remote release Terminal protection Protection against electric shock to A3, ÖVE-EN 6 Terminal type Lift terminals Ambient operating temperature - max 40 °C Ambient operating temperature - min -25 °C Assembly width 2 TE Enclosure width 80 mm Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 0 Number of poles at main contact unit - max 0 Number of switches (fault signal) 0 Rated operational current for specified heat dissipation (In) 0 A Voltage type....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-FW-MO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.