

INDUSTRIAL COMPONENT DATA

Z-FW-LPD 265244 Y7-265244 EATON ELECTRIC Restarting device, 24-48VDC, 4HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-FW-LPD



Manufacturer	EATON - MOELLER
MPN / Reference	Z-FW-LPD
Catalog number	Y7-265244
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-22A063E151
Generated	2026-08-05

Product Overview

Restarting device, 24-48VDC, 4HP

Z-FW-LPD

Eaton Distribution parts. Restarting device, 24-48VDC, 4HP

Restarting device, operational voltage 24-48V DC, frequency 50/60 Hz, functions: automatic restart, cap installation dimension 45mm, mounting width 4 SU (70mm), top-hat rail mounting, terminal cross-section 2x1.5 mm² or 1x2.5 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 265244 Model Code Z-FW-LPD EAN 4015082652449 Product

Length/Depth 80 mm Product Height 77.3 mm Product Width 88.4 mm Product Weight 0.247 kg Compliances RoHS

conform Product specifications

Used with Restarting device

Accessory for residual current circuit breaker

Accessory

Accessory for miniature circuit breaker Type Special features Z-FW... (Test module (0.5 space unit) for remote testing of residual current devices) Application Switchgear for industrial and advanced commercial applications Accessory/spare part type Restarting device Degree of protection IP40 Frame Standard front dimension: 45 mm Equipment heat dissipation, current-dependent 0 W Mounting method For fitting on right to: CLS6, PFIM, PFHM-4p, dRCM, Z-A40, PFR, Z-MS

Quick attachment with 2 latch positions on top-hat rail IEC/EN 60715 Additional equipment required Monitoring unit with automatic reclosing Terminal protection Protection against electric shock to BGV A3, ÖVE-EN 6 Terminal type Lift terminals Ambient operating temperature - max 40 °C Ambient operating temperature - min -25 °C Assembly width 4 TE Enclosure width 80 mm Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 0 Number of poles at main contact unit - max 0 Number of switches (fault signal) 0 Rated operational...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-FW-LPD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.