

INDUSTRIAL COMPONENT DATA

Z-FW-LPD/MO 290172 Y7-290172 EATON ELECTRIC

Restarting device-set, 24-48VDC, 6HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-FW-LPD/MO



Manufacturer	EATON - MOELLER
MPN / Reference	Z-FW-LPD/MO
Catalog number	Y7-290172
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-84DC6F6004
Generated	2026-08-06

Product Overview

Restarting device-set, 24-48VDC, 6HP

Z-FW-LPD/MO

Eaton Distribution parts. Restarting device-set, 24-48VDC, 6HP, LPD

Set consisting of restarting device and switch module, operational voltage 24-48V DC, frequency 50/60 Hz, functions: automatic restart, cap installation dimension 45mm, mounting width 6 SU (105mm), top-hat rail mounting, terminal cross-section 2x1.5 mm² or 1x2.5 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 290172 Model Code Z-FW-LPD/MO EAN 4015082901721 Product Length/Depth 80 mm Product Height 77.3 mm Product Width 123.4 mm Product Weight 0.324 kg Compliances RoHS conform Product specifications

Used with Restarting device - pre-assembled kits

Accessory for residual current circuit breaker

Accessory for miniature circuit breaker

Accessory Type Application Switchgear for industrial and advanced commercial applications Accessory/spare part type

Restarting device Equipment heat dissipation, current-dependent 0 W Mounting method For fitting on right to: CLS6, PFIM, PFHM-4p, dRCM, Z-A40, PFR, Z-MS Additional equipment required Monitoring unit with automatic reclosing Ambient

operating temperature - max 40 °C Ambient operating temperature - min -25 °C Assembly width 6 TE Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 0 Number of poles at main contact unit - max 0 Number of switches (fault signal) 0 Rated operational current for specified heat dissipation (In) 0 A Voltage type DC Functions With auto test for earth leakage function Monitoring unit with automatic reclosing Device fitting Universal Rated operational voltage (Ue) - max 48 V Rated switch current 0 A Static heat dissipation, non-current-dependent 0.8 W Suitable for current of main co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-FW-LPD/MO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.