

INDUSTRIAL COMPONENT DATA

DILM12-XR 110099 Y7-110099 EATON ELECTRIC Reversing bridge, for DILM7-M12

Brand: EATON - MOELLER | Manufacturer Part Number: DILM12-XR



Manufacturer	EATON - MOELLER
MPN / Reference	DILM12-XR
Catalog number	Y7-110099
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	20 Pcs
Document ID	EO-58AA99DAAF
Generated	2026-08-03

Product Overview

Reversing bridge, for DILM7-M12

DILM12-XR

Eaton Moeller® series DILM Reversing bridge, for DILM7-M12 DILM12-XR

Plug-in main current wiring bridge for quick, simple mounting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM reversing bridge Catalog Number 110099 Model Code DILM12-XR EAN 4015081096657 Product Length/Depth 90 mm Product Height 31 mm Product Width 7 mm Product Weight 0.013 kg

Compliances CE Marked Certifications UL 508

EN 60947-4-1

CSA Std. C22.2 No. 14-05

IEC 60947-4-1

UL Category Control No.: NLRV

UL File No.: E36332

CSA Class No.: 3211-05

UL

CSA

CSA-C22.2 No. 14-05

CSA File No.: 012528

IEC/EN 60947-4-1

CE Features & Functions

Functions To assemble reversing starters with tool-less plug connection General

Accessory/spare part type Connecting bridge Overvoltage category III Pollution degree 3 Rated impulse withstand voltage (Uimp) 6000 V AC Type Connection system SmartWire Used with DILM7-DILM12 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Electrical Rating

Rated operational voltage (Ue) at AC - min 230 V Rated operational voltage (Ue) at AC - max 415 V Design verification

Equipment heat dissipation, current-dependent Pvid 2.1 W Heat dissipation capacity Pdis 0 W Rated operational current

for specified heat dissipation (In) 22 A 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM12-XR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.