


INDUSTRIAL COMPONENT DATA

**DIULM25/21(230V50HZ,240V60HZ) 278161 Y7-278161 EATON
ELECTRIC Reversing contactor combination, 3p, +2S free,..**

Brand: EATON - MOELLER | Manufacturer Part Number: DIULM25/21(230V50HZ,240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DIULM25/21(230V50HZ,240V60HZ)
Catalog number	Y7-278161
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-DA8B7A7DBC
Generated	2026-08-06

Product Overview

Reversing contactor combination, 3p, +2S free, 11kW/400V/AC3

DIULM25/21(230V50HZ,240V60HZ)

Eaton Moeller® series DIUL Reversing contactor combination, 380 V 400 V: 11 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation

Reversing contactor combination, Application: Contactor combinations for starting motors with two directions of rotation, Accessories: DIUL reversing combinations, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Rated operational current AC-3 380 V 400 V: I_e = 25 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 7.5 kW, 380 V 400 V: P = 11 kW, 660 V 690 V: P = 14 kW, Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, Voltage AC/DC: AC operation, Notes: Also suitable for motors with efficiency class IE3. , IE3-ready devices are identified by the logo on their packaging.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DIUL contactor combination Catalog Number 278161 Model Code

DIULM25/21(230V50HZ,240V60HZ) EAN 4015082781613 Product Length/Depth 138 mm Product Height 85 mm Product Width 90 mm Product Weight 1.088 kg Compliances CE Marked

RoHS Compliant Certifications CSA Certified

UL Listed

IEC 60947-4-1

EN 60947-4-1

CE

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

UL

UL Category Control No.: NLDX

CSA

UL File No.: E29096

IEC/EN 60947-4-1

CSA Class No.: 2411-03, 3211-04

CSA File No.: 012528 Features & Functions

Features Mechanical interlock Functions Reversing safety Number Of Poles Three-pole General

Application Contactor combinations for starting motors with two directions of rotation Frame size 45 mm Product category

Contactor combinations Suitable for Also motors with efficiency class IE3 Type Full voltage reversing contactor Utilization category AC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Electrical Rating

Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 25 A Rated operational current (Ie) at AC-3, 380 V, 400 V, 415

V 25 A Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 25 A Rated operational power at AC-3, 380/400 V, 50

Hz 11 kW Rated operational power at AC-4, 220/230 V, 50 Hz 3.5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DIULM25/21(230V50HZ,240V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.