


INDUSTRIAL COMPONENT DATA

DIULM32/21(RDC24) 107026 Y7-107026 EATON ELECTRIC Reversing contactor combination, 3p, +2S free, 15kW/400V/A..

Brand: EATON - MOELLER | Manufacturer Part Number: DIULM32/21(RDC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DIULM32/21(RDC24)
Catalog number	Y7-107026
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-32D37A7BBB
Generated	2026-08-06

Product Overview

Reversing contactor combination, 3p, +2S free, 15kW/400V/AC3

DIULM32/21(RDC24)

Eaton Moeller® series DIUL Reversing contactor combination, 380 V 400 V: 15 kW, 24 V DC, DC operation

Reversing contactor combination, Application: Contactor combinations for starting motors with two directions of rotation, Accessories: DIUL reversing combinations, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Rated operational current AC-3 380 V 400 V: Ie= 32 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 10 kW, 380 V 400 V: P= 15 kW, 660 V 690 V: P= 17 kW, Actuating voltage: 24 V DC, Voltage AC/DC: DC operation, Notes: Also suitable for motors with efficiency class IE3. , IE3-ready devices are identified by the logo on their packaging.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DIUL contactor combination Catalog Number 107026 Model Code

DIULM32/21(RDC24) EAN 4015081067947 Product Length/Depth 138 mm Product Height 85 mm Product Width 90 mm

Product Weight 1.235 kg Certifications CSA Class No.: 2411-03, 3211-04

UL

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

CSA

CE

CSA File No.: 012528

UL Category Control No.: NLDX

IEC/EN 60947-4-1

UL File No.: E29096 Catalog Notes IE3-fähige Geräte sind mit dem Logo auf der Verpackung gekennzeichnet. Features & Functions

Features Mechanical interlock Functions Reversing safety General

Application Contactor combinations for starting motors with two directions of rotation Product category Contactor combinations Suitable for Also motors with efficiency class IE3 Utilization category AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-3: Normal AC induction motors: starting, switch off during running Voltage type DC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Electrical Rating

Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 32 A Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V 32 A Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 32 A Rated operational power at AC-3, 380/400 V, 50 Hz 15 kW Rated operational power at AC-4, 220/230 V, 50 Hz 4 kW Rated operational power at AC-4, 660/690 V, 50 Hz 10 kW Magnet system

Duty factor 100 % Rated c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DIULM32/21(RDC24) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.