

INDUSTRIAL COMPONENT DATA

**DIULM7/21(110V50HZ,120V60HZ) 278058 Y7-278058 EATON
ELECTRIC Reversing contactor combination, 3p, +2S free, ..**

Brand: EATON - MOELLER | Manufacturer Part Number: DIULM7/21(110V50HZ,120V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DIULM7/21(110V50HZ,120V60HZ)
Catalog number	Y7-278058
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-DD5656AF7F
Generated	2026-08-06

Product Overview

Reversing contactor combination, 3p, +2S free, 3kW/400V/AC3

DIULM7/21(110V50HZ,120V60HZ)

Eaton Moeller® series DIUL Reversing contactor combination, 380 V 400 V: 3 kW, 110 V 50 Hz, 120 V 60 Hz, AC operation

Reversing contactor combination, Application: Contactor combinations for starting motors with two directions of rotation,

Accessories: DIUL reversing combinations, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Rated operational current AC-3 380 V 400 V: I_e = 7 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 2.2 kW, 380 V 400 V: P = 3 kW, 660 V 690 V: P = 3.5 kW, Actuating voltage: 110 V 50 Hz, 120 V 60 Hz, Voltage AC/DC: AC operation, Notes: Also suitable for motors with efficiency class IE3. , IE3-ready devices are identified by the logo on their packaging.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DIUL contactor combination Catalog Number 278058 Model Code

DIULM7/21(110V50HZ,120V60HZ) EAN 4015082780586 Product Length/Depth 117 mm Product Height 68 mm Product

Width 90 mm Product Weight 0.591 kg Certifications CE

UL 60947-4-1

CSA File No.: 012528

CSA Class No.: 2411-03, 3211-04

UL
CSA
IEC/EN 60947-4-1
UL Category Control No.: NLDX
CSA-C22.2 No. 60947-4-1-14
UL File No.: E29096 Catalog Notes IE3-fähige Geräte sind mit dem Logo auf der Verpackung gekennzeichnet. Features & Functions
Features Mechanical interlock Functions Reversing safety General
Application Contactor combinations for starting motors with two directions of rotation Product category Contactor combinations Suitable for Also motors with efficiency class IE3 Utilization category AC-3: Normal AC induction motors: starting, switch off during running
AC-4: Normal AC induction motors: starting, plugging, reversing, inching Voltage type AC Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Electrical Rating
Rated operational current (I_e) at AC-1, 380 V, 400 V, 415 V 7 A Rated operational current (I_e) at AC-3, 380 V, 400 V, 415 V 7 A Rated operational current (I_e) at AC-1, 380 V, 400 V, 415 V 7 A Rated operational power at AC-3, 380/400 V, 50 Hz 3 kW Rated operational power at AC-4, 220/230 V, 50 Hz 1 kW Rated operational power at AC-4, 660/690 V, 50 Hz 2.9 kW
Magnet system
Duty factor 100 %...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DIULM7/21(110V50HZ,120V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.