

INDUSTRIAL COMPONENT DATA

**DIULEM/21/MV(230V50HZ,240V60HZ) 051849 Y7-51849 EATON
ELECTRIC Reversing contactor combination, 3p, +2S free..**

Brand: EATON - MOELLER | Manufacturer Part Number: DIULEM/21/MV(230V50HZ,240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DIULEM/21/MV(230V50HZ,240V60HZ)
Catalog number	Y7-51849
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-6287E2E0CC
Generated	2026-08-06

Product Overview

Reversing contactor combination, 3p, +2S free, 4kW/400V/AC3

Contactor Combination Inverter Screw Connection 3 Poles + 2 NO

Eaton Moeller® series DIULE Reversing contactor combination, 380 V 400 V: 4 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation

Reversing contactor combination, Application: Contactor combinations for starting motors with two directions of rotation, Accessories: DIUL reversing combinations, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Rated operational current AC-3 380 V 400 V: I_e = 9 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 2.2 kW, 380 V 400 V: P = 4 kW, 660 V 690 V: P = 4 kW, Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, Voltage AC/DC: AC operation, Notes: Also suitable for motors with efficiency class IE3. , IE3-ready devices are identified by the logo on their packaging.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DIULE contactor combination Catalog Number 051849 Model Code DIULEM/21/MV(230V50HZ,240V60HZ) EAN 4015080518495 Product Length/Depth 94 mm Product Height 61 mm Product Width 90 mm Product Weight 0.449 kg Certifications IEC/EN 60947-4-1

CSA

CSA Class No.: 3211-04

UL File No.: E29096

CSA-C22.2 No. 60947-4-1-14

UL

CE

CSA File No.: 012528

UL Category Control No.: NLDX

UL 60947-4-1 Features & Functions

Features Mechanical interlock Functions Reversing safety General

Application Contactor combinations for starting motors with two directions of rotation Product category Contactor

combinations Suitable for Also motors with efficiency class IE3 Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Electrical Rating

Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 9 A Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V

9 A Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 9 A Rated operational power at AC-3, 380/400 V, 50 Hz 4

kW Rated operational power at AC-4, 220/230 V, 50 Hz 1.5 kW Rated operational power at AC-4, 660/690 V, 50 Hz 3 kW

Magnet system

Duty factor 100 % Rated control supply voltage (Us) at AC, 50 Hz - min 230 V Rated control supply voltage (Us) at AC, 50

Hz - max 230 V Rated control supply voltage (Us) at AC, 60 Hz - min 240 V Rated control supply voltage (Us) at AC, 60 Hz

- max 240 V Rated control supp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DIULEM/21/MV(230V50HZ,240V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.