


INDUSTRIAL COMPONENT DATA

**DIULM17/21(110V50HZ,120V60HZ) 278133 Y7-278133 EATON
ELECTRIC Reversing contactor combination, 3p, +2S free,..**

Brand: EATON - MOELLER | Manufacturer Part Number: DIULM17/21(110V50HZ,120V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DIULM17/21(110V50HZ,120V60HZ)
Catalog number	Y7-278133
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-6ACB1CD7A1
Generated	2026-08-06

Product Overview

Reversing contactor combination, 3p, +2S free, 7.5kW/400V/AC3

DIULM17/21(110V50HZ,120V60HZ)

Eaton Moeller® series DIUL Reversing contactor combination, 380 V 400 V: 7.5 kW, 110 V 50 Hz, 120 V 60 Hz, AC operation

Reversing contactor combination, Application: Contactor combinations for starting motors with two directions of rotation, Accessories: DIUL reversing combinations, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Rated operational current AC-3 380 V 400 V: I_e = 18 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 5 kW, 380 V 400 V: P = 7.5 kW, 660 V 690 V: P = 11 kW, Actuating voltage: 110 V 50 Hz, 120 V 60 Hz, Voltage AC/DC: AC operation, Notes: Also suitable for motors with efficiency class IE3. , IE3-ready devices are identified by the logo on their packaging.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DIUL contactor combination Catalog Number 278133 Model Code

DIULM17/21(110V50HZ,120V60HZ) EAN 4015082781330 Product Length/Depth 138 mm Product Height 85 mm Product Width 90 mm Product Weight 1.082 kg Certifications UL 60947-4-1

CE

UL Category Control No.: NLDX

IEC/EN 60947-4-1

CSA-C22.2 No. 60947-4-1-14

UL File No.: E29096

CSA

CSA File No.: 012528

CSA Class No.: 2411-03, 3211-04

UL Catalog Notes IE3-fähige Geräte sind mit dem Logo auf der Verpackung gekennzeichnet. Features & Functions

Features Mechanical interlock Functions Reversing safety General

Application Contactor combinations for starting motors with two directions of rotation Product category Contactor

combinations Suitable for Also motors with efficiency class IE3 Utilization category AC-4: Normal AC induction motors:

starting, plugging, reversing, inching

AC-3: Normal AC induction motors: starting, switch off during running Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Electrical Rating

Rated operational current (I_e) at AC-1, 380 V, 400 V, 415 V 18 A Rated operational current (I_e) at AC-3, 380 V, 400 V, 415

V 18 A Rated operational current (I_e) at AC-1, 380 V, 400 V, 415 V 18 A Rated operational power at AC-3, 380/400 V, 50

Hz 7.5 kW Rated operational power at AC-4, 220/230 V, 50 Hz 2.5 kW Rated operational power at AC-4, 660/690 V, 50 Hz

6.5 kW Magnet system

Duty fact...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DIULM17/21(110V50HZ,120V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.