

INDUSTRIAL COMPONENT DATA

T3-5-71/E 004165 Y7-4165 EATON ELECTRIC Reversing multi-speed switches, Contacts: 10, 32 A, 2 speeds, 2 sepa..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-5-71/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-5-71/E
Catalog number	Y7-4165
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-8170F2003D
Generated	2026-08-03

Product Overview

Reversing multi-speed switches, Contacts: 10, 32 A, 2 speeds, 2 separate windings, front plate: 2-1-0-1-2, 60 °, maintained, flush mounting

Switch Multi-speed with reverse; 10-pole; 32; 2 speeds; 2 separate windings; rating Plate: 2-1-0-1-2; 60 °; Interlock; recessed Mounting

Eaton Moeller® series T3 Reversing multi-speed switches, T3, 32 A, flush mounting, 5 contact unit(s), Contacts: 10, 60 °, maintained, With 0 (Off) position, 2-1-0-1-2, Design number 71

Reversing multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 10, Degree of Protection: Front IP65, Design: flush mounting, switching function: 2 speeds, 2 separate windings, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-1-0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Reversing multi-speed switch Catalog Number 004165 Model Code T3-5-71/E
EAN 4015080041658 Product Length/Depth 125 mm Product Height 54 mm Product Width 61 mm Product Weight 0.292 kg
Certifications VDE 0660
UL

CE

IEC/EN 60947

UL File No.: E36332

CSA-C22.2 No. 60947-4-1-14

CSA File No.: 012528

IEC/EN 60947-3

CSA-C22.2 No. 94

UL Category Control No.: NLRV

UL 60947-4-1

CSA Class No.: 3211-05

IEC/EN 60204

CSA Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 004165 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Pole switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-5-71/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.