

INDUSTRIAL COMPONENT DATA

T3-7-68/E 005531 Y7-5531 EATON ELECTRIC Reversing multi-speed switches, Contacts: 13, 32 A, One tapped windi..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-7-68/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-7-68/E
Catalog number	Y7-5531
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-F22A5FFEAD
Generated	2026-08-04

Product Overview

Reversing multi-speed switches, Contacts: 13, 32 A, One tapped winding, 2 speeds, front plate: 2-1-0-1-2, 60 °, maintained, flush mounting, SOND 30

Switch Multi-speed with reverse; 13-pole; 32; 1 winding threading; 2 speeds; rating Plate: 2-1-0-1-2; 60 °; Interlock; recessed Mounting; SOND 30

Eaton Moeller® series T3 Reversing multi-speed switches, T3, 32 A, flush mounting, 7 contact unit(s), Contacts: 13, 60 °, maintained, With 0 (Off) position, 2-1-0-1-2, SOND 30, Design number 68

Reversing multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 30, Contacts: 13, Degree of Protection: Front IP65, Design: flush mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-1-0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Reversing multi-speed switch Catalog Number 005531 Model Code T3-7-68/E
EAN 4015080055310 Product Length/Depth 148 mm Product Height 54 mm Product Width 61 mm Product Weight 0.372 kg
Certifications IEC/EN 60204
IEC/EN 60947-3

UL

UL Category Control No.: NLRV

VDE 0660

CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

CSA Class No.: 3211-05

CE

CSA

UL File No.: E36332

CSA-C22.2 No. 94

IEC/EN 60947 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 005531 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

32 A

Rated operation current I_e at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF0073...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-7-68/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.