

**INDUSTRIAL COMPONENT DATA**

# T3-7-67/Z 005530 Y7-5530 EATON ELECTRIC Reversing multi-speed switches, Contacts: 14, 32 A, One tapped windi..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-7-67/Z



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T3-7-67/Z       |
| Catalog number  | Y7-5530         |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-C87F24DAD8   |
| Generated       | 2026-08-05      |

## Product Overview

Reversing multi-speed switches, Contacts: 14, 32 A, One tapped winding, 2 speeds, front plate: 2-1-0-1-2, 60 °, maintained, rear mounting, SOND 29

Switch Multi-speed with reverse; 14-pole; 32; 1 winding threading; 2 speeds; rating Plate: 2-1-0-1-2; 60 °; Interlocking; Installation bottom panel; SOND 29

Reversing multi-speed switches, T3, 32 A, rear mounting, 7 contact unit(s), Contacts: 14, 60 °, maintained, With 0 (Off) position, 2-1-0-1-2, SOND 29, Design number 67

Reversing multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 29, Contacts: 14, Degree of Protection: Front IP65, Design: rear mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-1-0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

## Additional Product Information

**General specifications**

Product Name Eaton Moeller® series T3 Reversing multi-speed switch Catalog Number 005530 Model Code T3-7-67/Z  
EAN 4015080055303 Product Length/Depth 190 mm Product Height 54 mm Product Width 61 mm Product Weight 0.406 kg  
Certifications CSA-C22.2 No. 60947-4-1-14  
CE

IEC/EN 60947-3

UL Category Control No.: NLRV

IEC/EN 60947

UL 60947-4-1

CSA File No.: 012528

VDE 0660

CSA

CSA-C22.2 No. 94

IEC/EN 60204

UL File No.: E36332

CSA Class No.: 3211-05

UL Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second

ETIM for 005530 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I<sub>u</sub> (EF001389)

32 A

Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-7-67/Z with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.