

INDUSTRIAL COMPONENT DATA

T3-7-67/Z 005530 Y7-5530 EATON ELECTRIC Reversing multi-speed switches, Contacts: 14, 32 A, One tapped windi..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-7-67/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-7-67/Z
Catalog number	Y7-5530
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-C87F24DAD8
Generated	2026-08-05

Product Overview

Reversing multi-speed switches, Contacts: 14, 32 A, One tapped winding, 2 speeds, front plate: 2-1-0-1-2, 60 °, maintained, rear mounting, SOND 29

Switch Multi-speed with reverse; 14-pole; 32; 1 winding threading; 2 speeds; rating Plate: 2-1-0-1-2; 60 °; Interlocking; Installation bottom panel; SOND 29

Reversing multi-speed switches, T3, 32 A, rear mounting, 7 contact unit(s), Contacts: 14, 60 °, maintained, With 0 (Off) position, 2-1-0-1-2, SOND 29, Design number 67

Reversing multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 29, Contacts: 14, Degree of Protection: Front IP65, Design: rear mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-1-0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Reversing multi-speed switch Catalog Number 005530 Model Code T3-7-67/Z
EAN 4015080055303 Product Length/Depth 190 mm Product Height 54 mm Product Width 61 mm Product Weight 0.406 kg
Certifications CSA-C22.2 No. 60947-4-1-14
CE

IEC/EN 60947-3

UL Category Control No.: NLRV

IEC/EN 60947

UL 60947-4-1

CSA File No.: 012528

VDE 0660

CSA

CSA-C22.2 No. 94

IEC/EN 60204

UL File No.: E36332

CSA Class No.: 3211-05

UL Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 005530 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

32 A

Rated operation current I_e at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-7-67/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.