

INDUSTRIAL COMPONENT DATA

T0-3-8451/XZ 013508 Y7-13508 EATON ELECTRIC

Changeoverswitches, Contacts: 6, 20 A, 45 °, rear mounting, Basi..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-8451/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-8451/XZ
Catalog number	Y7-13508
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-FAE627C1F3
Generated	2026-08-06

Product Overview

Changeoverswitches, Contacts: 6, 20 A, 45 °, rear mounting, Basic switch

Switch 6-pole 20 A Indicator plate: 0-1-2 60°

Changeoverswitches, T0, 20 A, rear mounting, Basic switch, 3 contact unit(s), Contacts: 6, 45 °, design no. 8451

Changeover switch, Product range: Control switches, Part group reference: T0, Contacts: 6, Design: rear mounting, Basic switch, Switching angle: 45 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

EL-Nummer (Norway)1456682Changeoverswitches, T0, 20 A, rear mounting, Basic switch, 3 contact unit(s), Contacts: 6, 45 °, design no. 8451Changeover switch, Product range: Control switches, Part group reference: T0, Contacts: 6, Design: rear mounting, Basic switch, Switching angle: 45 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeControl switchesPart group referenceT0Basic functionChangeoverswitchesContacts6Designrear mounting
Basic switchContact sequenceSwitching angle45 °Design number8451Front plate no.Motor rating AC-23A, 50 - 60 Hz
[P]400 V [P]5.5 kWRated uninterrupted current [Iu]20 ANote on rated uninterrupted current IuRated uninterrupted current

luis specified for max. cross-section.Number of contact units3 contact unit(s)Technical data
GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204
Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40
°COvervoltage category/pollution degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical shock
resistance15 gMounting positionAs requiredContactsElectrical characteristicsRated operational voltage [Ue]690 V
ACElectrical characteristicsRated uninterrupted current [Iu]20 AElec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-8451/XZ with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.