

INDUSTRIAL COMPONENT DATA

T0-4-8440/Z 048342 Y7-48342 EATON ELECTRIC Multi-speed switches, Contacts: 8, 20 A, One tapped winding, 2 sp..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-8440/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-8440/Z
Catalog number	Y7-48342
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-CAE6EB9DCC
Generated	2026-08-02

Product Overview

Multi-speed switches, Contacts: 8, 20 A, One tapped winding, 2 speeds, front plate: 0-1-2, 60 °, maintained, rear mounting
Multi-speed switch; 8 poles; 20 A; 1 threaded winding; 2

Multi-speed switches, T0, 20 A, rear mounting, 4 contact unit(s), Contacts: 8, 60 °, maintained, With 0 (Off) position, 0-1-2,
Design number 8440

Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate,
Contacts: 8, Degree of Protection: Front IP65, Design: rear mounting, switching function: One tapped winding, 2 speeds,
Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1-2, Motor rating AC-23A, 50 -
60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660,
IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Multi-speed switches, T0, 20 A, rear mounting, 4 contact unit(s), Contacts: 8, 60 °, maintained, With 0 (Off) position, 0-1-2,
Design number 8440Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip
and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: rear mounting, switching function: One tapped
winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1-2, Motor
rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 4 contact unit(s), Standards: IEC/EN
60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3
General specificationsProduct nameEaton Moeller® series T0 Multi-speed switchPart

no.T0-4-8440/ZEAN4015080483427Product Length/Depth147 millimetreProduct height48 millimetreProduct width48 millimetreProduct weight0.187 kilogramCertificationsCSA File No.: 012528

CSA

CSA Class No.: 3211-05

CSA-C22.2 No. 94

UL

UL Category Control No.: NLRV

VDE 0660

IEC/EN 60947

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-3

CE

IEC/EN 60204

UL File No.: E36332

CSA

ULProduct TradenameT0Product TypeMulti-speed switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsEnclosure materialPlasticFitted with:0 (off) position Black thumb grip and front plateInscription0-1-2Number of poles3Switch function typeOne tapped winding, 2 speedsGeneral in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-8440/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.