

INDUSTRIAL COMPONENT DATA

T0-5-15876/EZ 000900 Y7-900 EATON ELECTRIC Reversing star-delta switches, Contacts: 10, 20 A, front plate: D..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-5-15876/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-5-15876/EZ
Catalog number	Y7-900
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-FD5AF1F7F8
Generated	2026-08-04

Product Overview

Reversing star-delta switches, Contacts: 10, 20 A, front plate: D-Y-0-Y-D, 60 °, maintained, centre mounting

Star-Triangle Switch with 10-Pole Reversal 20 A Plate

Eaton Moeller® series T0 Reversing star-delta switches, T0, 20 A, center mounting, 5 contact unit(s), Contacts: 10, 60 °, maintained, With 0 (Off) position, D-Y-0-Y-D, Design number 15876

Turnaround star-delta switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 10, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: D-Y-0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Turnaround star-delta switch Catalog Number 000900 Model Code T0-5-15876/EZ
EAN 4015080009009 Product Length/Depth 134 mm Product Height 48 mm Product Width 48 mm Product Weight 0.201 kg

Certifications CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-3

CSA

IEC/EN 60204

UL

UL File No.: E36332

IEC/EN 60947

CSA Class No.: 3211-05

CE

CSA-C22.2 No. 94

VDE 0660

CSA File No.: 012528

UL Category Control No.: NLRV

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 000900 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Turnaround star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

20 A

Rated operation current I_e at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

5.5 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-5-15876/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.