

INDUSTRIAL COMPONENT DATA

T0-5-8043/XZ 014670 Y7-14670 EATON ELECTRIC Power factor meter changeover switch, Ie 12A, 90°, maintained, r..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-5-8043/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-5-8043/XZ
Catalog number	Y7-14670
Category	Voltmeter selector switch
Minimum order	1 Pcs
Document ID	EO-774FB0348A
Generated	2026-08-05

Product Overview

Power factor meter changeover switch, Ie=12A, 90°, maintained, replacement switch, base fixing

Switch Power Factor Meter Switch; 12A; 90 °; Spare switch for box

T0, 20 A, rear mounting, Basic switch, 5 contact unit(s), Contacts: 9, 90 °, design no. 8043

Cam switch according to IEC/EN60947, size T0, without handle, snap screw-floor fastener, rated uninterrupted current Iu 20A, rated operating voltage Ue 690V, deliverable accessories according to catalog information cam switch T. General designs: insulation-material add-on housing, flush mounting, center mounting, rear mounting IVS service distribution board mounting.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

T0, 20 A, rear mounting, Basic switch, 5 contact unit(s), Contacts: 9, 90 °, design no. 8043Cam switch according to IEC/EN60947, size T0, without handle, snap screw-floor fastener, rated uninterrupted current Iu 20A, rated operating voltage Ue 690V, deliverable accessories according to catalog information cam switch T. General designs: insulation-material add-on housing, flush mounting, centre mounting, rear mounting IVS service distribution board mounting.Delivery program

Product rangeControl switchesPart group referenceT0Contacts9Designrear mounting

Basic switchContact sequenceSwitching angle90 °Design number8043Front plate no.Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]5.5 kWRated uninterrupted current [Iu]20 ANote on rated uninterrupted current IuRated uninterrupted current Iuis specified for max. cross-section.Number of contact units5 contact unit(s)Technical data

General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open -25 - +50 °C Ambient temperature Enclosed -25 - +40

°C Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [Uimp] 6000 V AC Mechanical shock

resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [Ue] 690 V

AC Electrical characteristics Rated uninterrupted current [Iu] 20 A Electrical characteristics Note on rated uninterrupted current

Iu Rated...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-5-8043/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.