

INDUSTRIAL COMPONENT DATA

T0-6-15866/IVS 036477 Y7-36477 EATON ELECTRIC Reversing multi-speed switch, contacts: 12, 20 A, 2 speeds, 2 ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-6-15866/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	T0-6-15866/IVS
Catalog number	Y7-36477
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-9373F7FF49
Generated	2026-08-04

Product Overview

Reversing multi-speed switch, contacts: 12, 20 A, 2 speeds, 2 rotation directions,Dahlander,front plate:2-1-0-1-2, 60°,maintained,distr.board mounting

Multi-speed switch with 12-pole reversing 20 A 2 speeds

Eaton Moeller® series T0 Reversing multi-speed switches, T0, 20 A, service distribution board mounting, 6 contact unit(s), Contacts: 12, 60 °, maintained, With 0 (Off) position, 2-1-0-1-2, Design number 15866

Reversing multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 12, Degree of Protection: Front IP30, Design: service distribution board mounting, switching function: 2 speeds, 2 operating directions, One tapped winding, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-1-0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Reversing multi-speed switch Catalog Number 036477 Model Code

T0-6-15866/IVS EAN 4015080364771 Product Length/Depth 130 mm Product Height 55 mm Product Width 54 mm Product Weight 0.229 kg Certifications CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

UL File No.: E36332

CE

UL

CSA-C22.2 No. 94

VDE 0660

CSA

IEC/EN 60947

UL Category Control No.: NLRV

CSA File No.: 012528

IEC/EN 60204

IEC/EN 60947-3

CSA Class No.: 3211-05 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 036477 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP30

Degree of protection (NEMA), front side (EF011961)

2

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

Yes

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-6-15866/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.