

INDUSTRIAL COMPONENT DATA

T3-3-8622/E 020034 Y7-20034 EATON ELECTRIC Reversing switches, Contacts: 6, 32 A, front plate: Rückwärts-Hal..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-3-8622/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-3-8622/E
Catalog number	Y7-20034
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-4639696CC4
Generated	2026-08-02

Product Overview

Reversing switches, Contacts: 6, 32 A, front plate: Rückwärts-Halt-Vorwärts, 45 °, maintained, flush mounting, SOND 27 6-pole inverter switch 32 A Indicator plate:

Eaton Moeller® series T3 Reversing switches, T3, 32 A, flush mounting, 3 contact unit(s), Contacts: 6, 45 °, maintained, With STOP position, Rückwärts-Halt-Vorwärts, SOND 27, Design number 8622

Reversing switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 27, Contacts: 6, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With STOP position, front plate: Rückwärts-Halt-Vorwärts, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Reversing switch Catalog Number 020034 Model Code T3-3-8622/E EAN 4015080200345 Product Length/Depth 102 mm Product Height 54 mm Product Width 61 mm Product Weight 0.212 kg

Certifications UL 60947-4-1

VDE 0660

IEC/EN 60204

CE

IEC/EN 60947-3

CSA File No.: 012528

UL

UL File No.: E36332

CSA-C22.2 No. 94

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

CSA

CSA Class No.: 3211-05

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (I_{cs}) for a time of 1 second

ETIM for 020034 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing switch

Number of poles (EF001391)

2

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

32 A

Rated operation current I_e at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing materi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-3-8622/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.