

INDUSTRIAL COMPONENT DATA

T3-4-8419/E 020617 Y7-20617 EATON ELECTRIC Star-delta switches, Contacts: 7, 32 A, front plate: 0-Y-D, 90 °,...

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-8419/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-4-8419/E
Catalog number	Y7-20617
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-67813ADD96
Generated	2026-08-02

Product Overview

Star-delta switches, Contacts: 7, 32 A, front plate: 0-Y-D, 90 °, maintained, flush mounting, SOND 27

Star-Triangle Switch 7 poles 32 A Indicator plate: 0-Y-D

Eaton Moeller® series T3 Star-delta switches, T3, 32 A, flush mounting, 4 contact unit(s), Contacts: 7, 90 °, maintained, With 0 (Off) position, 0-Y-D, SOND 27, Design number 8419

Star-delta switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 27, Contacts: 7, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Star-delta switch Catalog Number 020617 Model Code T3-4-8419/E EAN 4015080206170 Product Length/Depth 114 mm Product Height 54 mm Product Width 61 mm Product Weight 0.252 kg

Certifications IEC/EN 60947-3

UL File No.: E36332

CSA

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

CSA-C22.2 No. 94

VDE 0660

IEC/EN 60947

UL Category Control No.: NLRV

CE

IEC/EN 60204

CSA File No.: 012528

CSA Class No.: 3211-05

UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 020617 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

18.5 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-8419/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.