

INDUSTRIAL COMPONENT DATA

T3-4-8440/EZ 000959 Y7-959 EATON ELECTRIC Multi-speed switches, Contacts: 8, 32 A, One tapped winding, 2 spe..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-8440/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-4-8440/EZ
Catalog number	Y7-959
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-20CE7EB8FB
Generated	2026-08-03

Product Overview

Multi-speed switches, Contacts: 8, 32 A, One tapped winding, 2 speeds, front plate: 0-1-2, 60 °, maintained, centre mounting

Multi-speed switch 8 poles 32 A 1 threaded winding 2

Eaton Moeller® series T3 Multi-speed switches, T3, 32 A, centre mounting, 4 contact unit(s), Contacts: 8, 60 °, maintained, With 0 (Off) position, 0-1-2, Design number 8440

Multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: center mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Multi-speed switch Catalog Number 000959 Model Code T3-4-8440/EZ EAN 4015080009597 Product Length/Depth 136 mm Product Height 54 mm Product Width 61 mm Product Weight 0.28 kg Certifications IEC/EN 60947

UL 60947-4-1

IEC/EN 60204

UL
CSA
CSA-C22.2 No. 60947-4-1-14
VDE 0660
UL File No.: E36332
CSA-C22.2 No. 94
CE
CSA Class No.: 3211-05
UL Category Control No.: NLRV
CSA File No.: 012528
IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 000959 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
Dahlander switch
Number of poles (EF001391)
3
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current Iu (EF001389)
32 A
Rated operation current Ie at AC-3, 400 V (EF001392)
23.7 A
Rated operation power at AC-3, 400 V (EF001364)
12 kW
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
No
Suitable for front mounting (EF007246)
Yes
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No
Complete device in housing (EF007317)

No
Housing mat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-8440/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.