

## INDUSTRIAL COMPONENT DATA

# T3-6-15877/E 023895 Y7-23895 EATON ELECTRIC Reversing star-delta switches, Contacts: 12, 32 A, front plate: ..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-6-15877/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T3-6-15877/E    |
| Catalog number  | Y7-23895        |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-E4BD6602E8   |
| Generated       | 2026-08-02      |

## Product Overview

Reversing star-delta switches, Contacts: 12, 32 A, front plate: D-Y-0-Y-D, 60 °, maintained, flush mounting

Star-Triangle Switch with Inversion; 12 poles; 32 A; Plaque

Eaton Moeller® series T3 Reversing star-delta switches, T3, 32 A, flush mounting, 6 contact unit(s), Contacts: 12, 60 °, maintained, With 0 (Off) position, D-Y-0-Y-D, Design number 15877

Turnaround star-delta switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 12, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: D-Y-0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I<sub>u</sub> = 32 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

## Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Turnaround star-delta switch Catalog Number 023895 Model Code T3-6-15877/E  
EAN 4015080238959 Product Length/Depth 137 mm Product Height 54 mm Product Width 61 mm Product Weight 0.332 kg

Certifications IEC/EN 60204

VDE 0660

CE

CSA

UL

UL 60947-4-1

UL Category Control No.: NLRV

CSA File No.: 012528

IEC/EN 60947-3

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

UL File No.: E36332

CSA Class No.: 3211-05

CSA-C22.2 No. 94 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 023895 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Turnaround star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

18.5 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-6-15877/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.