

INDUSTRIAL COMPONENT DATA

T5B-4-8441/I4 207236 Y7-207236 EATON ELECTRIC

Multi-speed switches, Contacts: 8, 63 A, One tapped winding, 2..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-4-8441/I4



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-4-8441/I4
Catalog number	Y7-207236
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-D4117656B7
Generated	2026-08-03

Product Overview

Multi-speed switches, Contacts: 8, 63 A, One tapped winding, 2 speeds, front plate: 1-0-2, 60 °, maintained, surface mounting

T5B-4-8441/I4

Eaton Moeller® series T5B Multi-speed switches, T5B, 63 A, surface mounting, 4 contact unit(s), Contacts: 8, 60 °, maintained, With 0 (Off) position, 1-0-2, Design number 8441

Multi-speed switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Contacts: 8, Degree of Protection: IP65, Design: surface mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 1-0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Multi-speed switch Catalog Number 207236 Model Code T5B-4-8441/I4 EAN 4015082072360 Product Length/Depth 240 mm Product Height 197 mm Product Width 160 mm Product Weight 1.435 kg Certifications CSA File No.: 012528

UL

UL 60947-4-1

UL File No.: E36332

IEC/EN 60947

IEC/EN 60204

CSA-C22.2 No. 94

IEC/EN 60947-3

CE

CSA

CSA Class No.: 3211-05

VDE 0660

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 207236 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

63 A

Rated operation current Ie at AC-3, 400 V (EF001392)

41 A

Rated operation power at AC-3, 400 V (EF001364)

37 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

Yes

Housing...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-4-8441/I4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.