

## INDUSTRIAL COMPONENT DATA

**T5B-4-8441/Z 092025 Y7-92025 EATON ELECTRIC Multi-speed switches, Contacts: 8, 63 A, One tapped winding, 2 s..**

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-4-8441/Z



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T5B-4-8441/Z    |
| Catalog number  | Y7-92025        |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-4F64995390   |
| Generated       | 2026-08-05      |

**Product Overview**

Multi-speed switches, Contacts: 8, 63 A, One tapped winding, 2 speeds, front plate: 1-0-2, 60 °, maintained, rear mounting

Multi-speed switch 8 poles 63 A 1 threaded winding 2

Eaton Moeller® series T5B Multi-speed switches, T5B, 63 A, rear mounting, 4 contact unit(s), Contacts: 8, 60 °, maintained, With 0 (Off) position, 1-0-2, Design number 8441

Multi-speed switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: rear mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 1-0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I<sub>u</sub> = 63 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |                                                  |
|--------------|--------------------------------------------------|
| Catalog path | EATON - MOELLER > Disconnectors and Cam Switches |
|--------------|--------------------------------------------------|

**Additional Product Information**

## General specifications

Product Name Eaton Moeller® series T5B Multi-speed switch Catalog Number 092025 Model Code T5B-4-8441/Z EAN 4015080920250 Product Length/Depth 182 mm Product Height 88 mm Product Width 88 mm Product Weight 0.769 kg

Certifications CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

UL File No.: E36332

UL

UL 60947-4-1

CE

UL Category Control No.: NLRV

VDE 0660

IEC/EN 60947

CSA-C22.2 No. 94

CSA Class No.: 3211-05

CSA

IEC/EN 60947-3

CSA File No.: 012528 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 092025 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

63 A

Rated operation current Ie at AC-3, 400 V (EF001392)

41 A

Rated operation power at AC-3, 400 V (EF001364)

37 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Housing ma...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-4-8441/Z with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.