

INDUSTRIAL COMPONENT DATA

T5B-5-15876/Z 214786 Y7-214786 EATON ELECTRIC

Reversing star-delta switches, Contacts: 10, 63 A, front plate..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-5-15876/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-5-15876/Z
Catalog number	Y7-214786
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-9AF9737FBB
Generated	2026-08-05

Product Overview

Reversing star-delta switches, Contacts: 10, 63 A, front plate: D-Y-0-Y-D, 60 °, maintained, rear mounting, SOND 28
T5B-5-15876/Z

Eaton Moeller® series T5B Reversing star-delta switches, T5B, 63 A, rear mounting, 5 contact unit(s), Contacts: 10, 60 °, maintained, With 0 (Off) position, D-Y-0-Y-D, SOND 28, Design number 15876

Turnaround star-delta switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Notes: SOND 28, Contacts: 10, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: D-Y-0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Turnaround star-delta switch Catalog Number 214786 Model Code
T5B-5-15876/Z EAN 4015082147860 Product Length/Depth 198 mm Product Height 88 mm Product Width 88 mm Product
Weight 0.904 kg Certifications IEC/EN 60947

UL File No.: E36332

UL Category Control No.: NLRV

UL

CSA Class No.: 3211-05

IEC/EN 60204

IEC/EN 60947-3

CSA-C22.2 No. 60947-4-1-14

VDE 0660

CSA-C22.2 No. 94

CE

CSA File No.: 012528

UL 60947-4-1

CSA Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 214786 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Turnaround star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

63 A

Rated operation current Ie at AC-3, 400 V (EF001392)

41 A

Rated operation power at AC-3, 400 V (EF001364)

37 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-5-15876/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.