

INDUSTRIAL COMPONENT DATA

T5B-5-SOND*/Z 907972 Y7-907972 EATON ELECTRIC

Non-standard switch, T5B, 63 A, rear mounting, 5 contact unit(.

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-5-SOND*/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-5-SOND*/Z
Catalog number	Y7-907972
Category	Switch disconnecter
Minimum order	10 Pcs
Document ID	EO-2F36C72276
Generated	2026-08-05

Product Overview

Non-standard switch, T5B, 63 A, rear mounting, 5 contact unit(s)

T5B-5-SOND*/Z

Non-standard switch, Product range: Non-standard switch, Part group reference: T5B, Notes: customized version according to form, Degree of Protection: Front IP65, Design: rear mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Non-standard switch, T5B, 63 A, rear mounting, 5 contact unit(s)Non-standard switch, Product range: Non-standard switch, Part group reference: T5B, Notes: customized version according to form, Degree of Protection: Front IP65, Design: rear mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

General specificationsProduct nameEaton Moeller® series T5B Non-standard switchPart no.T5B-5-SOND*/ZProduct

Length/Depth198 millimetreProduct height88 millimetreProduct width88 millimetreProduct weight0.904

kilogramCertificationsIEC/EN 60947-3

IEC/EN 60204

VDE 0660

IEC/EN 60947 Product Tradename T5B Product Type Non-standard switch Product Sub Type None Catalog Notes Customized version according to form

Rated Short-time Withstand Current (I_{cw}) for a time of 1 second General information Degree of protection NEMA 12 Degree of protection (front side) IP65 Lifespan, mechanical 500,000 Operations Mounting method Rear mounting Mounting position As required Number of contact units 5 Operating frequency 1200 Operations/h Overvoltage category III Pollution degree 3 Rated impulse withstand voltage (U_{imp}) 6000 V AC Safe isolation 440 V AC, Between the contacts, According to EN 61140 Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms Suitable for Intermed...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-5-SOND*/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.