

## INDUSTRIAL COMPONENT DATA

# T5B-7-15866/E 214788 Y7-214788 EATON ELECTRIC

## Reversing multi-speed switch, contacts: 12, 63 A, 2 speeds, 2

..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-7-15866/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T5B-7-15866/E   |
| Catalog number  | Y7-214788       |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-8F7BC500CD   |
| Generated       | 2026-08-02      |

## Product Overview

Reversing multi-speed switch, contacts: 12, 63 A, 2 speeds, 2 rotation directions, Dahlander, front plate: 2-1-0-1-2, 45°, maintained, flush mounting

T5B-7-15866/E

Eaton Moeller® series T5B Reversing multi-speed switches, T5B, 63 A, flush mounting, 7 contact unit(s), Contacts: 12, 45 °, maintained, With 0 (Off) position, 2-1-0-1-2, Design number 15866

Reversing multi-speed switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Contacts: 12, Degree of Protection: Front IP65, Design: flush mounting, switching function: 2 speeds, 2 operating directions, One tapped winding, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-1-0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

## Additional Product Information

## General specifications

Product Name Eaton Moeller® series T5B Reversing multi-speed switch Catalog Number 214788 Model Code

T5B-7-15866/E EAN 4015082147884 Product Length/Depth 190 mm Product Height 88 mm Product Width 88 mm Product Weight 1.13 kg Certifications CSA-C22.2 No. 94

UL File No.: E36332

CSA Class No.: 3211-05

UL 60947-4-1

VDE 0660

IEC/EN 60204

CSA File No.: 012528

UL

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

IEC/EN 60947-3

CSA

CE

IEC/EN 60947 Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second

ETIM for 214788 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I<sub>u</sub> (EF001389)

63 A

Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392)

41 A

Rated operation power at AC-3, 400 V (EF001364)

37 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF00...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-7-15866/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.